PROGard 08DE Dry Erase Laminating Film

Description

PROGard 08DE Dry Erase is a clear polyester laminating film with a dry erase coating.

Recommended Applications

For long-term dry erase marking capabilities on smooth sealed surfaces including wall calendars, communication boards, and printed graphics. It can be written on repeatedly and wiped clean with a dry tissue or dry erase cleaning solution. For indoor use only.

Technical Data

Material	Polyester with a dry erase coating
Thickness (without liner and adhesive)	1 mil
Colour	Transparent
Gloss (@ 60°)	90
Adhesive	Clear, permanent, pressure sensitive, acrylic
Adhesive Strength	180° Peel, Stainless Steel, 24 hr: 2.5 lb/in
Release Liner	78# paper
Outdoor Durability (based on proper application	Not recommended for outdoor use; Up to 2 years
procedures on vertical surfaces)	indoors
Minimum Application Temperature	50°F (10°C)
Temperature Resistance	-40°F to +180°F (-40°C to +82°C)
Chemical Resistance	Resistant to 10% ammonium hydroxide, detergent,
	distilled water, gasoline, and 10% hydrochloric acid.
Shelf Life	2 years from date of manufacture
Available Sizes	24" x 50yd, 30" x 50, 54" x 50yd

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. All data are based upon research which the Company believes to be reliable but does not constitute warranty. The purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use.



