

## Description

PROPrint 202Y is a digitally printable monomeric PVC film with a grey adhesive. It is specially designed to be compatible with UV printers. Available in white with a gloss finish.

## Recommended Applications

For flat short-term indoor and outdoor applications including branding, packaging, and general signage.

## Technical Data

Material	Calendered monomeric PVC
Thickness (without liner and adhesive)	3 mil
Colour	White
Dimensional Stability	<1% after application
Seawater Resistance	No variation (100 hours at 23°C, aluminum plate)
Adhesive	Grey, permanent, pressure sensitive, solvent-based
Adhesive Strength	FTM1 180° peel, steel 24 hr: 2.7 lb/in Release Force: 0.06 lb/in
Release Liner	84# single PE-coated silicon paper
Print Compatibility	Solvent, eco-solvent, UV-curable, latex, screen printing
Outdoor Durability (based on proper application procedures on vertical surfaces)	Up to 1 year (unprinted)
Minimum Application Temperature	48°F (9°C)
Temperature Resistance	-5°F to 158°F (-20°C to 70°C)
Shelf Life	2 years from ship date
Available Sizes	54" x 50yd

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. All data are based upon research which the Company believes to be reliable but does not constitute warranty. The purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use.