

Description

PROPrint 202Y is a digitally printable monomeric PVC film with a grey adhesive. Available in white with a gloss or matte finish.

Recommended Applications

For flat short-term indoor and outdoor applications including branding, packaging, and general signage.

Technical Data

Material	Calendered monomeric PVC
Thickness (without liner and adhesive)	3.1 mil
Colour	White
Dimensional Stability	FTM14 (steel plate): <1% after application
Seawater Resistance	DIN 50021 (48 hours at 23°C, glass plate): No variation
Tensile Strength	ASTM D882-02 Along: min 3480 psi Across: min 3335 psi
Elongation at break	ASTM D882-02 Along: min 140% Across: min 180%
Adhesive	Grey, permanent, pressure sensitive, solvent-based
Adhesive Strength	FTM1 (180° peel, steel, 24 hr): 2.2-3.1 lb/in
Release Liner	74# single PE-coated silicon paper
Print Compatibility	Solvent, eco-solvent, UV-curable, latex, screen printing
Outdoor Durability (based on proper application procedures on vertical surfaces)	Up to 1 year (unprinted)
Minimum Application Temperature	50°F (10°C)
Temperature Resistance	-5°F to 150°F (-20°C to 65C)
Shelf Life	2 years from ship date
Available Sizes	30" x 55yd, 54" x 55yd, 60" x 55yd

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. All data are based upon research which the Company believes to be reliable but does not constitute warranty. The purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use.



www.expresssignproducts.com
 customerservice@expresssignproducts.com
 1-800-461-1722