

Description

PROGard 260C Optically Clear is an optically clear polyester UV laminating film.

Recommended Applications

For protecting digitally printed graphics from UV fading, abrasion, dust, and weather. Designed to be clear at a distance – no distortion or blur. Ideal for protecting printed glass graphics, especially perforated window films. Reduced dimple effect on window perf compared to typical cast laminating films. For flat surfaces only.

Technical Data

Material	Polyester
Thickness (without liner and adhesive)	1 mil
Colour	Transparent
Gloss (@ 60°)	125
Adhesive	Optically clear, permanent, pressure sensitive, acrylic
Adhesive Strength	180° Peel, Stainless Steel 15 min: 2.3 lb/in 24 hr: 31 lb/in
Release Liner	1 mil polyester
Outdoor Durability (based on proper application procedures on vertical surfaces)	Up to 2 years
Minimum Application Temperature	40°F (4°C)
Temperature Resistance	0°F to 140°F (-17°C to +60°C)
Chemical Resistance	Resistant to 10% ammonium hydroxide, antifreeze, detergent, distilled water, gasoline, and SAE 20 motor oil.
Shelf Life	2 years from date of manufacture
Available Sizes	27" x 33yd, 54" x 33yd

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. All data are based upon research which the Company believes to be reliable but does not constitute warranty. The purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use.



Express Sign Products – West
1116 Macleod Street
Pincher Creek, AB T0K 1W0
800-461-1722

Express Sign Products – East
5 Industrial Road
St. Marys, ON N4X 1G2
800-461-1722