

Description

PROCling printable static cling is a digitally printable cling film available in clear or white. Removable and reapplicable without adhesive.

Recommended Applications

For short-term indoor graphics on glass or other hard polished surfaces. Ideal for window graphics, windshield stickers, and glass displays.

Technical Data

| | |
|--|--|
| Material | Static cling vinyl |
| Winding Direction | Print-side out |
| Thickness (without liner and adhesive) | White: 7 mil Transparent: 8 mil |
| Colour | White or transparent |
| Gloss (@ 60°) | 95 |
| Adhesive | Static electricity |
| Release Liner | White: 10 pt coated cardstock Transparent: 8 pt coated cardstock |
| Print Compatibility | Solvent, eco-solvent, latex, UV-curable |
| Outdoor Durability (based on proper application procedures on vertical surfaces) | Indoor use only |
| Minimum Application Temperature | 20°F (-6°C) |
| Temperature Resistance | 0°F to 175°F (-18°C to +80°C) |
| Chemical Resistance | Resistant to detergent and distilled water. Poor resistance to alkalis, mild acids, most petroleum-based oil, grease, aliphatic solvents, and salts. |
| Shelf Life | 1 year from date of manufacture |
| Available Sizes | 24" x 25yd, 30" x 25yd, 54" x 25yd |

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. All data are based upon research which the Company believes to be reliable but does not constitute warranty. The purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use.



Express Sign Products – West
1116 Macleod Street
Pincher Creek, AB T0K 1W0
800-461-1722

Express Sign Products – East
5 Industrial Road
St. Marys, ON N4X 1G2
800-461-1722