

Description

PROPrint 201Y is a digitally printable monomeric PVC film with a grey adhesive. Available in white with a gloss or matte finish.

Recommended Applications

For flat short-term indoor and outdoor applications including branding, packaging, and general signage.

Technical Data

Material	Calendered monomeric PVC
Thickness (without liner and adhesive)	3 mil
Colour	White
Dimensional Stability (FTM14)	Max 0.5mm (48 hours at 70°C, aluminum plate, MD)
Seawater Resistance	No variation (100 hours at 23°C, aluminum plate)
Adhesive	Grey, permanent, pressure sensitive, solvent-based
Adhesive Strength	FTM1 180° peel, steel 2 hr: 2.2 lb/in 24 hr: 2.9 lb/in Release Force: 0.09 lb/in
Release Liner	74# single PE-coated silicon paper
Print Compatibility	Solvent, eco-solvent, UV-curable, latex, screen printing
Outdoor Durability (based on proper application procedures on vertical surfaces)	Up to 2 years (unprinted)
Minimum Application Temperature	48°F (9°C)
Temperature Resistance	5°F to 158°F (-15°C to 70°C)
Shelf Life	2 years from date of manufacture
Available Sizes	30" x 50yd, 54" x 50yd, 60" x 50yd

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. All data are based upon research which the Company believes to be reliable but does not constitute warranty. The purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use.



Express Sign Products – West
1116 Macleod Street
Pincher Creek, AB T0K 1W0
800-461-1722

Express Sign Products – East
5 Industrial Road
St. Marys, ON N4X 1G2
800-461-1722